

OVA8® POWER POLE

Streamline® OVA8® High Pressure Power Pole a unique high pressure configuration for the OVA8® Poles but for high pressure cleaning, enabling users to clean up 42ft with 4000psi 276bar. And because of the anti-spin pole section on the Streamline® OVA8® pole, the oval shaped clamps work less due to only having to prevent the pole sections from moving up or down. The pole offers more rigidity and better control, as the two flat sides sits more comfortably in an operator's hand and allow the tips of their fingers to sit on the flat edge.

This product is really a cost-effective cleaning solution. It eliminates the need for additional cleaning equipment, such as ladders or scaffolding, which can be costly and time-consuming. Overall, the Streamline® Power Pole is an excellent investment for anyone who needs a reliable and efficient cleaning tool for hard-to-reach areas.

A very easy adjustable pole with high pressure adaption allows for operator to clean hard to reach area with ease and with the comfortable handle design, support user with reducing fatigue and strain on arms and back during extended cleaning operations.

Build with high quality carbon fibre and stainless components, the Pole can withstand heavy use and rugged durability which supports long lasting investment into another Streamline® product.

Features

- Water pressure up to 4000psi/276bar.
- Pole heights up 25ft, 29ft, 33ft and 42ft.
- Anti-twist pole.
- Lightweight carbon poles.
- More rigidity and better control.



Think you could benefit from an OVA8® Power Pole?
Call our sales team on +44 (0) 1626 830 830

	HP-OV4-COMP	HP-OV5-COMP	HP-OV6-COMP	HP-OV8-COMP
Pole Material	Carbon Composite (100% Carbon, except glass fibre handle)			
Number of Sections:	4	5	6	8
Minimum Length:	2000mm	2070mm	2280mm	2320mm
Achievable Height:	25ft	29ft	33ft	42ft
Weight	4.28kg	4.62kg	5.02kg	7.2kg
Sturdy Trigger attached firmly to the pole section (can be adjusted) with hose swivel and quick release fitting	Fitted	Fitted	Fitted	Fitted
High Pressure/Temperature Rating	276bar/100°C	276bar/100°C	276bar/100°C	276bar/100°C
Clamp System	OVA8® Clamp	OVA8® Clamp	OVA8® Clamp	OVA8® Clamp