

DF10-F-001

FEATURES

- The FILTERPLUS® DF10-F water filters reduce extra fine dirt, sand, sediment, silt, rust particles, and scale particles.
- The FILTERPLUS® DF10-F water filter is resistant to chemicals and corrosion.
- The DF10 filter cartridge is designed for purity, bacteria resistance, and chemical resistance.
- The FILTERPLUS® DF10-F spun fibers form a true gradient density from outer to inner surfaces.
- The FILTERPLUS® DF10-F replacement water filter will not impart taste, odor or color to the liquid being filtered when used within the recommended temperature limit.
- The coreless strength of the FILTERPLUS® DF10-F water filter cartridge is achieved by sintering the many fibers into a solid matrix.
- The FILTERPLUS® DF10-F filter is a 5 micron extra fine sediment water filter cartridge made of spun bonded polypropylene.
- The FILTERPLUS® DF10-F water filters are manufactured from 100% pure polypropylene.
- The FILTERPLUS® DF10-F water filters can be used on chlorinated or non-chlorinated water supplies.
- The FILTERPLUS® DF10-F water filter cartridges fit in whole house water filter systems and Reverse Osmosis Systems.
- The FILTERPLUS® DF10-F is Tested and Certified by NSF International to NSF/ANSI Standard 42 for material requirements only.



Used In Brands	FILTERPLUS®
Manufacturer's Id	DF10-F
Advertised Size (in)	10 x 2-1/2
Actual Size (in)	9 3/4 inches (length) x 2 3/8 inches (outside diameter)
Actual Size (cm)	24.77 x 6.0325
Media	Spun Wound Polypropylene
Primary Filter Media	Polypropylene
Filter Life (gallons)	8,000
Filter Life (liters)	30,283.28
Filter Life (months)	2 months
Micron Rating (Nominal)	5
Operating Temperature (°F)	40 - 145
Operating Temperature (°C)	4.4 - 62.8
Flow Rate (gpm)	5
Flow Rate (lpm)	18.927

PLEASE NOTE: Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system.

WHAT DOES THE DRAGONFLY® 4 INCLUDE?

- 600-ml-Tank im Rucksack
- Sicheres Akku-Pumpen-Gehäuse mit beleuchtetem Ein-/Ausschalter
- 230-Volt-Ladegerät
- Gepolsterter Rucksack für den DRAGONFLY®
- Druckschalter zur Bedienung an der Teleskopstange
- Mopp-Aufsatz mit Feinsprühfunktion
- 2 x Mikrofaser-Scheuerpad
- 2 x Mikrofaser-Polierpad
- Tasche zur sicheren Aufbewahrung des Rucksackkits



OPERATING SPECIFICATIONS

Gewicht ohne Wasser	1.5kg
Gewicht mit Wasser	2.1kg
Akku - NiMH	12V
Akku-Laufzeit	10 Stunden
Akkuladedauer	10 Stunden

DRAGONFLY® 4 TELESKOPSTANGEN

XR70™ Carbon-Teleskopstange mit innengeführtem Spiralschlauch*, tropffreier Sprühdüse und verstellbarem Winkeladapter.

*Hinweis: Bei Stangen mit einer Länge von über 8,5 m ist der Schlauch außen.



OPERATING SPECIFICATIONS

DRAGON-XR70-405200	5.5mtr/20ft extended length	1.09kg
DRAGON-XR70-406000	6.4mtr/23ft extended length	1.22kg
DRAGON-XR70-507300	7.6mtr/27ft extended length	1.61kg
DRAGON-XR70-608500	8.5mtr/31ft extended length	2.03kg
DRAGON-XR70-709700	9.7mtr/35ft extended length	2.45kg
DRAGON-XR70-810800	10.8mtr/38ft extended length	2.62kg
DRAGON-XR70-713200	13.2mtr/46ft extended length	2.84kg
DRAGON-XR70-814800	14.8mtr/52ft extended length	3.32kg
DRAGON-XR70-816500	16.5mtr/57ft extended length	3.61kg

reinline
reinline KG
Am Knick 7
22113 Oststeinbek

Tel: 040 - 71 48 66-0
Fax: 040 - 71 48 66-10