

SMARTANK™ 2

(RODI) Dual Operator Flat tank systems

- ✓ Stainless Steel Cabinets
- ✓ System Flush
- ✓ Flow metre tracking
- ✓ Improved flow
- ✓ Upgraded Pre filters
- ✓ Easy DI vessel changes
- ✓ Enhanced TDS Meters
- ✓ Pressure Washer Take off
- ✓ LED Lighting



UPGRADED PRE-FILTERS

The Smartank 2 uses our more efficient, larger Filterplus® 10" Sediment cartridge filters & Carbon Block filters.



Introducing Smartank™ 2, the evolution in flat tank pure water delivery systems. We've taken our proven, crash-tested baffled tank design and infused it with smarter features that put you in control. The advanced baffling minimises water movement during transit, enhancing stability and safety at every turn.

Smartank™ 2 features integrated reverse osmosis and deionised filtration, removing minerals, contaminants and impurities from the water, delivering a streak free, professional window clean.

With built-in TDS meters and flow meters, you'll know exactly when filters need changing, saving you time and hassle.

Plug and play pumps and easy-access DI filters streamline your maintenance, while enhanced lighting and clear on/off controls mean effortless operation day or night.

Stainless steel cabinets deliver water proof lasting durability and sleek professional style. Smartank™ 2 isn't just an improved cleaning system, it's your competitive edge, enhancing the way you work.

Filterplus® 10" Sediment & Carbon Block filters are larger than previous model and deliver 20% more flow maximising speed and efficiency for pure water output into the tank.

Built-in flush functions extend filter life and keep performance at its peak, while the smart design ensures reliable, efficient operation day after day.

Smartank™ 2 also has a dedicated pressure washing take off, allowing you to conveniently supply a pressure washer directly from the tank system.

Specification	Smartank™ 2 400 (RODI)	Smartank™ 2 650 (RODI)
Country of Origin	United Kingdom	United Kingdom
Maximum Height	440mm	440mm
Maximum Length	1671mm	2090mm
Maximum Width	1215mm	1215mm
Tank Capacity	407 litres	585 litres
Dry Weight	150kg	172kg
Wet Weight	556 kg	757 kg
Min. Inlet pressure Requirement	2.8 / 40 bar / psi	2.8 / 40 bar / psi
Optimum operating pressure	6.9 / 100 bar / psi	6.9 / 100 bar / psi
Standard water inlet connection (Male hose lock)	¾ inch	¾ inch
Waste water outlet connection (Male hose lock)	¾ inch	¾ inch
Pure water outlet connection (Male hose lock)	¾ inch	¾ inch
Electrical Power supply	12v Battery / 230V mains	12v Battery / 230V mains
Optimum water quality	000ppm	000ppm
Water quality range	000ppm - 1000ppm	000ppm - 1000ppm
Pure Water Output (Optimal Conditions)	4.5ltr per pump	4.5ltr per pump
Operating time	Approx. 10hrs	Approx. 10hrs
Product code	SMT400SS-16	SMT650SS-16

*Performance figures are based on lab testing. Actual results may vary.



Inside the Smarttank™ 2

